

r o c k y r o c h o n (p) a i n t

SEMI-GLOSS: Approx. Coverage 370 sq.ft @1.5 dry mils, Vol. Solids 33.2%, Density 10.3# per gl.
This product is a premium 100% acrylic exterior semi-gloss sheen paint for wood siding and trim. Formulated to give rich color depth, with excellent color retention and coverage. Makes an ideal finish for showcase buildings or any commercial or residential building where the highest level of quality is desired.

Drying time: One hour to touch, and two hours for recoat at 70°F and 50% relative humidity. Do not apply when surface or air temperatures are below 35°F or when temperatures are expected to drop.

Coverage: Approximately 345 to 395 sq. ft. per gallon. Two coats recommended for even coverage. Coverage depends on porosity and profile of surface and can be less when making significant change in color.

Disposal: Never pour left over material down any sink or drain. Use up material on the job, or seal can and store safely for future use. Do not incinerate closed containers. For specific disposal guidelines contact your local waste management agency.

Cleanup: Remove all paint spatters, and wash all brushes and equipment immediately with warm soapy water. Follow with a clear rinse.

Warning!: If you scrape, sand, or remove old paint, you may release lead dust. Lead is toxic. Exposure to lead dust can cause serious illness, such as brain damage, especially in children. Pregnant women should also avoid exposure. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the national lead information hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

California
Proposition

65 warning: This product contains a chemical known to the state of California to cause cancer, birth defects or other reproductive harm.

Caution: Do not take internally. Close container after each use. When applied by spray application use proper mask for protection against inhalation of paint. Keep out of reach of children.

Health 1, Flammability 0, Reactivity 0, personal protection 0.

Product category VOC: Exterior Semi-Gloss does not exceed 50 grams/liter.



Manufactured for Rocky Rochon Paint, Seattle, WA
www.rockyrochonpaint.com